



TOWN OF RIVERHEAD

Yvette Aguiar, Supervisor

200 Howell Avenue

Riverhead, New York 11901-2596

631-727-3200

BID FOR: POLICE UNIFORM ITEMS

BIDDERS NAME

BIDDERS ADDRESS

CITY, STATE, ZIP

(_____) _____
PHONE NUMBER

EMAIL ADDRESS

In compliance with your advertisement for bids to be opened on **September 9, 2021** and subject to all conditions thereof, the undersigned hereby proposes to furnish the item(s) and/or service(s) itemized in this proposal in accordance with the Notice to Bidders, General Information Agreement and Specifications contained herein on the Bid Proposal Form attached.

Bidder certifies that the prices quoted herein do not include Federal Excise Tax or any Federal, New York State or City Sales Tax and are not higher than prices charged to any governmental or commercial consumer for like merchandise and/or service; and all prices include shipping and freight charges to any Municipal building or site within the Town of Riverhead.

Respectfully submitted,

Signature

Printed Name/Title

Date

THIS PAGE MUST BE COMPLETED, SIGNED, AND RETURNED WITH BID

**TOWN OF RIVERHEAD
NOTICE TO BIDDERS**

Sealed bids for **POLICE UNIFORM ITEMS** will be received by the Town Clerk of the Town of Riverhead at Town Hall, 200 Howell Avenue, Riverhead, New York, 11901, until **11:00 a.m.** on **September 9, 2021**, at which time all bids received shall be opened and read aloud.

Bid Specifications and/or Plans may be obtained by visiting the Town of Riverhead website at **www.townofriverheadny.gov** on or after **August 26, 2021**. Click on "Bid Requests" and follow the instructions to register.

All bids are to be submitted in a sealed envelope bearing the designation **POLICE UNIFORM ITEMS**. All bids must be submitted on the bid form provided. Any and all exceptions to the Specifications must be listed on a separate sheet of paper, bearing the designation "**EXCEPTIONS TO THE SPECIFICATIONS**" and be attached to the bid form.

NOTE: Bid responses must be delivered to the Office of the Town Clerk at 200 Howell Avenue, Riverhead, New York, 11901, on or before September 9, 2021 at 11:00 a.m. The Town may decline to accept, deem untimely and/or reject any bid response/proposal that is not delivered to the Office of the Town Clerk.

The Town Board reserves the right and responsibility to reject any or all bids or to waive any formality if it believes such action to be in the best interest of the Town.

BY ORDER OF THE TOWN BOARD

OF THE TOWN OF RIVERHEAD

DIANE M. WILHELM, TOWN CLERK

TOWN OF RIVERHEAD BID SPECIFICATION

GENERAL SPECIFICATIONS

Bidders shall be responsible to carefully examine the Specifications enclosed.

Bidders shall furnish their price as called for on the Bid Proposal Sheet(s) attached.

Alternates or equal of superior design and/or quality shall be listed separately and a Manufacturer's Specification Sheet shall be submitted with a bid. Failure to submit such data may result in the disallowing of said bid.

All things not expressly mentioned in these specifications, but involved in carrying out their intent are required by these Specifications; and the vendor shall perform the same as though they were specifically mentioned, described and delineated.

COMPLIANCE WITH RULES AND REGULATIONS

The unit and associated equipment furnished shall comply with all provisions which would be applicable, if the Town of Riverhead were a private corporation of Federal and State of New York Laws, Ordinances, Codes, Rules, Regulations, Orders, Permits and Licenses and with fire underwriters requirement, except that where the weight and dimensions requirements set forth herein exceed such provisions, these Specifications shall control.

DEVIATION

Minor deviations from the provisions of these Specifications will be considered to permit manufacturers to follow their standard manufacturing process.

Such deviations will be approved, however, only in the sole discretion of the Town of Riverhead and only if in its opinion they do not adversely affect the operation, maintenance, strength, efficiency, effectiveness, or life of the unit or any of its parts.

All proposed minor deviations, with full details, must be listed on a separate Detail Sheet, which must be attached to and made part of this bid.

The Town of Riverhead reserves the absolute right in its sole discretion to accept that bid, if any, which under all circumstances will best serve the public interest.

PRICES

If a like or lower quantity of a standard item contained in this bid is sold by a vendor at a price less than the prices quoted herein, the price to the Town of Riverhead shall be reduced to that lower price.

QUANTITY

The Town of Riverhead is in no way obligated to purchase quantities neither shown nor limited to said quantities listed.

CONTRACT PERIOD

The Contract Period shall be effective for a period of **ONE YEAR FROM DATE OF AWARD.** At the end of the contract period, the contract may be extended (not to exceed two (2) extensions for a one (1) year period each) upon the same terms and conditions at the sole discretion of the Town of Riverhead and with the consent of the vendor or vendors. The Town also reserves the right to cancel this contract at any time without notice.

RESERVATIONS

The mention in the specifications of any unit, component, or equipment by brand name and/or model is meant to convey to the potential bidder the type and quality of the product required and desired by the town. Any unit, component, or equipment which is of equal type and quality may be considered as such and may be acceptable to the town, upon agreement by the Town Board to that fact. The decision of the Town Board, however, in such a circumstance is final.

Furthermore, the Town Board of the Town of Riverhead reserves the right and responsibility to reject any or all bids if they believe such action to be in the best interest of the Town.

FUEL SURCHARGES

The Town of Riverhead will not pay any type of fuel surcharge. Any fuel charges added will be deleted from any payments made to the vendor.

The bidder shall also upon request file certification from each manufacturer relative to authorization, representation, delivery, service, warranties and guarantees for each product bid.

THE TOWN OF RIVERHEAD SHALL NOT BE RESPONSIBLE FOR ANY RESTOCKING FEES AND/OR CHARGES.

PURCHASE ORDERS MUST BE FILLED WITHIN 45 DAYS AFTER RECEIPT OF SAME.

BID SPECIFICATIONS / PROPOSAL / ACCEPTANCE SHEET

MUST BE COMPLETED, SIGNED, AND RETURNED WITH BID

INQUIRIES

Questions pertaining to this Bid should be directed in writing at least 5 business days before the bid opening date to the Town of Riverhead Purchasing Agent at baldinucci@townofriverheadny.gov . Telephone inquiries will not be accepted.

I/WE FULLY UNDERSTAND THAT THE ACCEPTANCE OF THIS BID IS SUBJECT TO THE PROVISIONS OF SECTION 103A AND 103B OF THE GENERAL MUNICIPAL LAW.

NAME OF AGENT/DEALER

ADDRESS

CITY, STATE, ZIP CODE

CONTACT PERSON (PRINT PLEASE)

PHONE NUMBER

EMAIL ADDRESS

DATE

SIGNATURE OF DEALER/AGENT

**Item #1: CX360 Female Covert Cargo
Pants Elbeco Style E3454LC**

Style: Pants are made with the Ladies Choice pattern, featuring a contour waistband with elastic side panels, shortened rise and reshaped hip and seat. Pants have a plain front, gusset, two back pockets, two covert cargo pockets with interior compartments, and a cellphone pocket on the wearer's left side.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 6.3 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Pockets

Front: Notched front pocket openings are a minimum 6½" and 6" deep from the bottom of each opening. Inside facing is a separate piece of self-material finishing no less than 1" wide. Bottom of each opening is reinforced with a patch of self-cloth that extends to the top edge of the hidden cargo pocket seam to hold a clip knife. Left pocket has a security pocket set in the pocket bag, closed with a 7" invisible zipper. Pockets are top-stitched, clean finished and have straight bar-tacks.

Back: Back pockets have minimum openings of 5" on size 8 and below, 5½" on sizes 10 and above and are 6" deep. They are made with a ½" single besom piece set to the bottom of each pocket opening and have straight bar-tacks.

Cellphone: A cellphone pocket on the wearer's left side that measures 4" wide x 6" deep is set 3½" below the front pocket, 2" from the finished sideseam. Pocket is made with a ½" single besom piece set to the bottom of the opening and has straight bar-tacks.

Side: Two covert cargo pockets sewn to the outside leg seams, set 9" below the bottom of the waistband, are made with ½" single besom welts. Internal pockets are constructed of pocketing fabric, measure 7" wide x 9" deep, and close with a 7" zippers. Inside each internal pocket is a patch pocket measuring 3¾" x 5½".

Pocketing: To be black 65% polyester/35% cotton with a minimum thread count of 70 x 48, weighing 4.3 oz. per square yard.

Waistband: Ladies Choice construction provides superior comfort and performance. There are 3¾" elastic sewn into each side of the waistband for superior fit.

Waistband curtain is made of black, bias-cut, cotton-blended twill and ½" shirt retention strip. Waistband is constructed using the closed method and measures 2" wide when finished. Finished waistband is fused and all stress points are bar-tacked. Waistband is set on and stitched below the lower edge through the outer fabric and the waistband curtain.

CX360 Female Covert Cargo Pants
Elbeco Style E3454LC

Waistband is closed with a metal spring snap with a textured matte finish snap cap. Inside waistband has a button and buttonhole adjacent to the snap for reinforcement. Center front closure is interlined to support the fabric and snap.

Belt Loops: There are a minimum of five lined belt loops on sizes 8 and below and seven on sizes 10 and above. Each loop is 1" wide of double-thickness with stitching on a face side 1/4" from each edge. Except for the back loop, which is tacked on, all loops are sewn into the bottom of the waistband and into the rocap. They accommodate a 1 $\frac{5}{8}$ " belt.

Inside Trim: Right fly lining is the same fabric and color as the waistband curtain. A non-woven interlining is sewn to the fly for additional stability and strength. Right fly lining is sewn to the left fly below the zipper.

A fully gusseted crotch made from the trouser fabric provides comfort and mobility. Gusset is set in a diamond shape, measuring 11 $\frac{3}{4}$ " long, point-to-point, by 2 $\frac{3}{4}$ " wide at center. Gusset is set evenly, front to back, with a 5-thread safety stitch and then edge-stitched.

Zippers: Trousers are closed with a gun metal zipper and have a brass bottom stop at the base of the zipper chain. A straight bar-tack is sewn through the outside of the garment to the inside at the bottom of the fly. It is sewn through the zipper tape, the right and left fly, and the right fly lining. Right and left fly are joined by an additional bar-tack located below the bottom zipper stop on the inside of the trouser.

Creasing: Front and back creases in both trouser legs must be applied via a pneumatically controlled application of Creaset silicone sealant, specially formulated for technologically enhanced fabrics to give permanency to the creases for the life of the garment.

Seams: Entire trouser is seamed with polyester core or 100% polyester spun thread. Seat seam is stitched with five-thread safety stitch.

Hemming: All trousers to have finished hemmed bottoms.

Labels: There is a heat seal label on the left hip pocket bag containing the brand, care, content, and size. An outside waistband label is marked with lot number, size, fiber content, cut number and UPC Identification.

Finishing and Pressing:

All loose threads are removed. Trousers must be pressed completely and properly with sideseam, inseam and seat seam pressed open. There must be a Jetclip attached to the top fly of the finished trouser.

CX360 Female Covert Cargo Pants Elbeco Style E3454LC

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	2	4	6	8	10	12	14
Waist relaxed	26½	27½	28½	29½	30½	32	33½
Waist stretched	29½	30½	31½	32½	33½	35	36½
Seat	36¼	37¼	38¼	39¼	40¼	41¼	43¼
Front Rise	8	8¼	8½	8¾	9	9¼	9½
Back Rise	14⁵/₈	14⁷/₈	15¹/₈	15³/₈	15⁵/₈	15⁷/₈	16¹/₈
Inseam	35	35	35	35	35	35	35

Size:	16	18	20	22	24	26	28
Waist relaxed	35	37	39	41	43	45	47
Waist stretched	38	40	42	44	46	48	50
Seat	44³/₄	46³/₄	48³/₄	50³/₄	52³/₄	54³/₄	56³/₄
Front Rise	9¾	10	10¼	10½	10¾	11	11½
Back Rise	16³/₈	16⁷/₈	16⁷/₈	17¹/₈	17³/₈	17⁷/₈	17⁷/₈
Inseam	35	35	35	35	35	35	35

February 22, 2021

**Item #2: CX360 Male Covert Cargo
Pants Elbeco Style E3444R**

Style: Pants are made with the Essential Fit uniform pattern with a plain front, gusset, two back pockets, two covert cargo pockets with internal compartments, and a cellphone pocket on the wearer's left side.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 6.3 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Pockets

Front: Notched front pocket openings are a minimum 6½" and 6½" deep from the bottom of each opening. Inside facing is a separate piece of self-material finishing no less than 1" wide. Bottom of each opening is reinforced with a patch of self-cloth that extends to the top edge of the hidden cargo pocket seam to hold a clip knife. Left pocket has a security pocket set in the pocket bag, closed with a 7" invisible zipper. Pockets are top-stitched, clean finished and have straight bar-tacks.

Back: Back pockets have minimum openings of 6" and are 6" deep. They are made with a ½" single besom piece set to the bottom of each pocket opening and have straight bar-tacks.

Cellphone: A cellphone pocket on the wearer's left side that measures 4" wide x 6" deep is set 5¼" below the back pocket, 2" from the finished sideseam. Pocket is made with a ½" single besom piece set to the bottom of the opening and has straight bar-tacks.

Side: Two covert cargo pockets sewn to the outside leg seams, set 10" below the bottom of the waistband, are made with ½" single besom welts. Internal pockets are constructed of pocketing fabric, measuring 7" wide x 9" deep, and close with 7" zippers. Inside each internal pocket is a patch pocket measuring 3¾" x 5½".

Pocketing: To be black 65% polyester/35% cotton with a minimum thread count of 70 x 48, weighing 4.3 oz. per square yard.

Waistband: Lightweight covert waistband contains an elastic extension, providing up to 3" of additional stretch. Front of the outer waistband tapers through the covert opening at the top of the front pocket opening. The 1¼" wide elastic extends from the end of the taper through the waistband behind the sideseam.

Waistband curtain is made of black, bias-cut, cotton-blended twill and ½" shirt retention strip. Waistband is constructed using the closed method and measures 2" wide when finished. Finished waistband is fused and all stress points are bar-tacked. Waistband is set on and stitched below the lower edge through the outer fabric and the waistband curtain.

CX360 Male Covert Cargo Pants Elbeco Style E3444R

Waistband is closed with a metal spring snap with a textured matte finish snap cap. Inside waistband has a button and buttonhole adjacent to the snap for reinforcement. Center front closure is interlined to support the fabric and snap.

Belt Loops: There are a minimum of five lined belt loops on sizes 30 and below, seven on sizes 31 through 48, and nine on sizes 50 and above. Each loop is 1" wide of double-thickness with stitching on a face side 1/4" from each edge. Except for the back loop, which is tacked on, all loops are sewn into the bottom of the waistband and into the rocap. They accommodate a 1 $\frac{5}{8}$ " belt.

Inner Fly/Crotch:

Right fly lining is the same fabric and color as the pocketing fabric. A non-woven interlining is sewn to the fly for additional stability and strength. Right fly lining is sewn to the left fly below the zipper.

A fully gusseted crotch made from the trouser fabric provides comfort and mobility. Gusset is set in a diamond shape, measuring 15" long, point-to-point, by 3 $\frac{1}{2}$ " wide at center. Gusset is set evenly, front to back, with a 5-thread safety stitch and then edge-stitched.

Zippers: Trousers are closed with a gun metal zipper and have a brass bottom stop at the base of the zipper chain. A straight bar-tack is sewn through the outside of the garment to the inside at the bottom of the fly. It is sewn through the zipper tape, the right and left fly, and the right fly lining. Right and left fly are joined by an additional bar-tack located below the bottom zipper stop on the inside of the trouser.

Creasing: Front and back creases in both trouser legs must be applied via a pneumatically controlled application of Creaset silicone sealant, specially formulated for technologically enhanced fabrics to give permanency to the creases for the life of the garment.

Seams: Entire trouser is seamed with polyester core or 100% polyester spun thread. Seat seam is stitched with five-thread safety stitch.

Hemming: All trousers to have finished hemmed bottoms.

Labels: There is a heat seal label on the left hip pocket bag containing the brand, care, content, and size. An outside waistband label is marked with lot number, size, fiber content, cut number and UPC Identification.

Finishing and Pressing:

All loose threads are removed. Trousers must be pressed completely and properly with sideseam, inseam and seat seam pressed open. There must be a Jetclip attached to the top fly of the finished trouser.

CX360 Male Covert Cargo Pants
Elbeco Style E3444R

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	28	29	30	31	32	33	34	35	36	37
Waist relaxed	28½	29½	30½	31½	32½	33½	34½	35½	36½	37½
Waist stretched	31½	32½	33½	34½	35½	36½	37½	38½	39½	40½
Seat	38¾	40¾	41¾	42¾	43½	44¾	45¾	46¾	47¼	48
Front Rise	9¼	9¾	9½	9¾	9¾	9¾	10	10¾	10¾	10½
Back Rise	14¾	14¾	15	15¾	15¾	15¾	15½	15¾	15¾	16
Inseam	37	37	37	37	37	37	37	37	37	37

Size:	38	40	42	44	46	48	50	52	54	56
Waist relaxed	38½	40½	42½	44½	46½	48½	50½	52½	54½	56½
Waist stretched	41½	43½	45½	47½	49½	51½	53½	55½	57½	59½
Seat	48¾	50¾	51¾	53½	55	56¾	58¾	60	61¾	63¾
Front Rise	10¾	11	11¾	11¾	12	12¾	12¾	13	13¾	13¾
Back Rise	16¾	16½	16¾	17¼	17¾	17¾	18¼	18¾	19	19¾
Inseam	37	37	37	37	37	37	37	37	37	37

February 22, 2021

**Item # 3: CX360 Female Long Sleeve
Shirt Elbeco Style 3534LC**

Style: It is the intention of this department to secure a tailored shirt equal in quality of workmanship and style to the shirt now on display as a sample. Shirt is cut on a form-fitting line, and the shape of the pockets and general style conform to this sample.

Tailoring: It is imperative that this garment is constructed according to the principles set forth in the specifications. All stitches must be of the proper tension and size to avoid puckering after the shirt has been laundered and give best durable press performance. All sewing is with Dacron core thread to match shirt fabric. Collar and cuffs are single-stitched $\frac{1}{4}$ " from edge. Pockets and flaps are single-stitched on the edge.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 4.5 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Collar: Convertible collar is one piece, measures 3" long at points and $1\frac{5}{8}$ " wide at back and is constructed of two plies of basic material and one ply of interlining. Collar lining is banana-shaped. Collar stays are of good quality vinyl that measure $2\frac{1}{2}$ " long x $\frac{3}{8}$ " wide and are attached to the bottom collar.

Sleeves: To be straight and whole. Cuffs are $2\frac{5}{8}$ " wide and fasten with two-button adjustable cuffs. There is a single stitch $\frac{7}{16}$ " from top of cuff. Sleeve opening measures $4\frac{1}{2}$ " from top of cuff. Top facing for this opening is 1" wide and bottom facing finishes about $\frac{1}{2}$ " wide.

Sleeves must be secured to the body of the shirt by a merrow stitch with a safety stitch to properly strengthen the stitch. The same stitch is used on the side closing seams.

Flex Vent: Flex Vent is made from 92% polyester/8% spandex mesh. Diamond-shaped mesh measuring $2\frac{1}{2}$ " wide x 8" long is set into the sleeve and body panels at the underarm to allow body heat ventilation, increased mobility, and comfort.

Front: Front has a facing 3" wide extending from the neckline to bottom of shirt provided by a turnunder of material. Right front has a lined false top center $1\frac{1}{2}$ " wide, finished, running full length of the shirt with two rows of stitching $\frac{7}{8}$ " apart. Center front contains seven vertical buttonholes placed $\frac{3}{4}$ " from edge; first at neck, second $2\frac{1}{2}$ " down and the balance $3\frac{1}{2}$ " apart. The 3rd, 4th, 5th, and 6th buttons are sewn on the top center and are not functional.

Left front has a button piece, $\frac{7}{8}$ " wide, stitched the full length. The first and 6th buttons are securely attached to the button piece and correspond to the buttonholes in

CX360 Female Long Sleeve Shirt
Elbeco Style 3534LC

the center front.

Zipper: A 14" nylon zipper is sewn to the front, positioned below the second button to replace the 3rd through 6th buttons.

Dual Comm Access Openings:

Access openings measuring 1½" are set in each side seam 1" below the bottom tip of the Flex Vent. Pouch-style openings are clean-finished, neatly concealed, and reinforced for durability. Openings are used to thread communication wires under the front of the shirt to keep them out of the way.

Pockets: Two double-entry chest pockets with mitered corners finish 5" wide x 5½" long. Side entry forms a utility pocket closed with Velcro. Both pockets have 1¼" box-pleats stitched from top to bottom to prevent spreading.

Flaps: Two scalloped flaps that finish 5¼" long, 2¾" wide at center and 2½¾" wide at sides are secured to front of shirt with two rows of stitching approximately ¼" above top of pocket. Flaps are interlined and have 1¼" wide pencil openings. A matching button and buttonhole are sewn on each flap.

Flap Closure: Side points of the flaps are secured to the pockets by Velcro fasteners sewn onto the flaps and pockets.

Badge Tab: Reinforced on inside of the shirt by a strip of material, 1½" wide, stitched and folded so that no raw edges show. Reinforcement strip extends from the flap setting stitch to the joining seam at the front of the yoke. There are two small horizontal buttonholes 1¼" apart with the bottom hole 1½" above top of left flap.

Mic Tab: A mic tab measuring ¾" x 2" is set 3½" below the center of the neckline.

Name Tape: An optional loose name tape measuring 7/8" wide x 8" long is set inside the right front pocket.

Buttons: All buttons, size 20 ligne, are made from high impact melamine and must match fabric.

Shoulder Straps:

Shoulder straps are pointed at the end toward the neck of the shirt. The other end is sewn in the sleeve head seam. Pointed ends are fastened with one matching button. Straps measure 2" at sleeve and taper to 1¾," and are set about 2" from the collar. Shoulder straps are box-stitched to shoulders with a row of cross-stitching 2" from sleeve head seam. There is a 1" concealed opening under the shoulder straps, set halfway between the neck seam and shoulder seam, to thread communication wires.

Back: Yoke, composed of an outer piece of the same material as the basic shirt and an inner piece of poplin, is joined at the side seams with 5-thread safety stitches.

**CX360 Female Long Sleeve Shirt
Elbeco Style 3534LC**

Permanent Creases:

Shirt has permanent military creases. Creases are stitched in shirt only, not through pockets and flaps. One crease in each front extends from hem to joining seam. Three vertical creases are in back; middle crease is on the center line and side creases are spaced equally from the center crease.

Creasing: Pockets and pocket flaps are die-creased to give uniform shape and size.

Interlining: Collar, cuffs, flaps, and top center are lined with non-fusible interlining for this 4-way stretch fabric.

Emblems: One Riverhead Town Police shoulder emblem shall be neatly sewn by vendor with matching thread on each left and right sleeve, $\frac{1}{2}$ " below the shoulder seam. When applicable one Sergeant chevron shall be sewn by vendor $\frac{1}{4}$ " below each Riverhead Town Police emblem. All emblems to be supplied by Police Department.

Labels: There is a heat-seal label containing brand, size, content, and country of origin in the yoke. Care label with cut number is sewn in the inside sideseam. Descriptive product hang tag is attached to front of shirt.

Pressing and Packing:

Shirts are carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are bulk-packed and shipped in strong boxes so as not to be damaged in shipment.

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	32	34	36	38	40	42	44	46	48	50
Neck Size	13 $\frac{1}{2}$	14	14 $\frac{1}{2}$	15	15 $\frac{1}{2}$	16	16 $\frac{1}{2}$	17	17 $\frac{1}{2}$	18
Chest	39 $\frac{1}{2}$	41	42 $\frac{1}{2}$	44	45 $\frac{1}{2}$	47 $\frac{1}{2}$	49 $\frac{1}{2}$	51 $\frac{1}{2}$	53 $\frac{1}{2}$	55 $\frac{1}{2}$
Waist	36 $\frac{1}{2}$	38	39 $\frac{1}{2}$	41	42 $\frac{1}{2}$	44 $\frac{1}{2}$	46 $\frac{1}{2}$	49 $\frac{1}{2}$	50 $\frac{1}{2}$	52 $\frac{1}{2}$
Back Length	27 $\frac{1}{2}$	28 $\frac{1}{2}$	29	29	29					
Sleeve Length	30	31	32	32	33	33	33	34	34	34

**Item #4: CX360 Female Short Sleeve
Shirt Elbeco Style 3554LC**

Style: It is the intention of this department to secure a tailored shirt equal in quality of workmanship and style to the shirt now on display as a sample. Shirt is cut on a form-fitting line, and the shape of the pockets and general style conform to this sample.

Tailoring: It is imperative that this garment is constructed according to the principles set forth in the specifications. All stitches must be of the proper tension and size to avoid puckering after the shirt has been laundered and give best durable press performance. All sewing is with Dacron core thread to match shirt fabric. Collar and cuffs are single-stitched $\frac{1}{4}$ " from edge. Pockets and flaps are single-stitched on the edge.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 4.5 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Collar: Convertible collar is one piece, measures 3" long at points and $1\frac{5}{8}$ " wide at back and is constructed of two plies of basic material and one ply of interlining. Collar lining is banana-shaped. Collar stays are of good quality vinyl that measure $2\frac{1}{2}$ " long x $\frac{3}{8}$ " wide and are attached to the bottom collar.

Sleeves: To be straight and whole, have 1" hems and finish $9\frac{1}{2}$ " long from shoulder seams. Sleeves must be secured to the body of the shirt by a merrow stitch with a safety stitch to properly strengthen the stitch. The same stitch is used on the side closing seams.

Flex Vent: Flex Vent is made from 92% polyester/8% spandex mesh. Diamond-shaped mesh measuring $2\frac{1}{2}$ " wide x 8" long is set into the sleeve and body panels at the underarm to allow body heat ventilation, increased mobility, and comfort.

Front: Front has a facing 3" wide extending from the neckline to bottom of shirt provided by a turnunder of material. Right front has a lined false top center $1\frac{1}{2}$ " wide, finished, running full length of the shirt with two rows of stitching $\frac{7}{8}$ " apart. Center front contains seven vertical buttonholes placed $\frac{3}{4}$ " from edge; first at neck, second $2\frac{1}{2}$ " down and the balance $3\frac{1}{2}$ " apart. The 3rd, 4th, 5th, and 6th buttons are sewn on the top center and are not functional.

Left front has a button piece, $\frac{7}{8}$ " wide, stitched the full length. The first and 6th buttons are securely attached to the button piece and correspond to the buttonholes in the center front.

Zipper: A 14" nylon zipper is sewn to the front, positioned below the second button to replace the 3rd through 6th buttons.

CX360 Female Short Sleeve Shirt Elbeco Style 3554LC

Dual Comm Access Openings:

Access openings measuring 1½" are set in each side seam 1" below the bottom tip of the Flex Vent. Pouch-style openings are clean-finished, neatly concealed, and reinforced for durability. Openings are used to thread communication wires under the front of the shirt to keep them out of the way.

Pockets: Two double-entry chest pockets with mitered corners finish 5" wide x 5½" long. Side entry forms a utility pocket closed with Velcro. Both pockets have 1¼" box-pleats stitched from top to bottom to prevent spreading.

Flaps: Two scalloped flaps that finish 5¼" long, 2¾" wide at center and 2½¾" wide at sides are secured to front of shirt with two rows of stitching approximately ¼" above top of pocket. Flaps are interlined and have 1¼" wide pencil openings. A matching button and buttonhole are sewn on each flap.

Flap Closure: Side points of the flaps are secured to the pockets by Velcro fasteners sewn onto the flaps and pockets.

Badge Tab: Reinforced on inside of the shirt by a strip of material, 1½" wide, stitched and folded so that no raw edges show. Reinforcement strip extends from the flap setting stitch to the joining seam at the front of the yoke. There are two small horizontal buttonholes 1¼" apart with the bottom hole 1½" above top of left flap.

Mic Tab: A mic tab measuring ¾" x 2" is set 3½" below the center of the neckline.

Name Tape: An optional loose name tape measuring 7/8" wide x 8" long is set inside the right front pocket.

Buttons: All buttons, size 20 ligne, are made from high impact melamine and must match fabric.

Shoulder Straps:

Shoulder straps are pointed at the end toward the neck of the shirt. The other end is sewn in the sleeve head seam. Pointed ends are fastened with one matching button. Straps measure 2" at sleeve and taper to 1¾," and are set about 2" from the collar. Shoulder straps are box-stitched to shoulders with a row of cross-stitching 2" from sleeve head seam. There is a 1" concealed opening under the shoulder straps, set halfway between the neck seam and shoulder seam, to thread communication wires.

Back: Yoke, composed of an outer piece of the same material as the basic shirt and an inner piece of poplin, is joined at the side seams with 5-thread safety stitches.

Permanent Creases:

Shirt has permanent military creases. Creases are stitched in shirt only, not through pockets and flaps. One crease in each front extends from hem to joining seam. Three vertical creases are in back; middle crease is on the center line and side creases are spaced equally from the center crease.

CX360 Female Short Sleeve Shirt
Elbeco Style 3554LC

Creasing: Pockets and pocket flaps are die-creased to give uniform shape and size.

Interlining: Collar, cuffs, flaps, and top center are lined with non-fusible interlining for this 4-way stretch fabric.

Emblems: One Riverhead Town Police shoulder emblem shall be neatly sewn by vendor with matching thread on each left and right sleeve, $\frac{1}{2}$ " below the shoulder seam. When applicable one Sergeant chevron shall be sewn by vendor $\frac{1}{4}$ " below each Riverhead Town Police emblem. All emblems to be supplied by Police Department.

Labels: There is a heat-seal label containing brand, size, content, and country of origin in the yoke. Care label with cut number is sewn in the inside sideseam. Descriptive product hang tag is attached to front of shirt.

Pressing and Packing:

Shirts are carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are bulk-packed and shipped in strong boxes so as not to be damaged in shipment.

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	32	34	36	38	40	42	44	46	48	50
Neck Size	13 $\frac{1}{2}$	14	14 $\frac{1}{2}$	15	15 $\frac{1}{2}$	16	16 $\frac{1}{2}$	17	17 $\frac{1}{2}$	18
Chest	39 $\frac{1}{2}$	41	42 $\frac{1}{2}$	44	45 $\frac{1}{2}$	47 $\frac{1}{2}$	49 $\frac{1}{2}$	51 $\frac{1}{2}$	53 $\frac{1}{2}$	55 $\frac{1}{2}$
Waist	36 $\frac{1}{2}$	38	39 $\frac{1}{2}$	41	42 $\frac{1}{2}$	44 $\frac{1}{2}$	46 $\frac{1}{2}$	49 $\frac{1}{2}$	50 $\frac{1}{2}$	52 $\frac{1}{2}$
Back Length	27 $\frac{1}{2}$	28 $\frac{1}{2}$	29	29	29					

February 12, 2021

**Item #5: CX360 Male Long Sleeve
Shirt Elbeco Style 3524**

Style: It is the intention of this department to secure a tailored shirt equal in quality of workmanship and style to the shirt now on display as a sample. Shirt is cut on a form-fitting line, and the shape of the pockets and general style conform to this sample.

Tailoring: It is imperative that this garment is constructed according to the principles set forth in the specifications. All stitches must be of the proper tension and size to avoid puckering after the shirt has been laundered and give best durable press performance. All sewing is with Dacron core thread to match shirt fabric. Collar and cuffs are single-stitched $\frac{1}{4}$ " from edge. Pockets and flaps are single stitched on the edge.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 4.5 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Collar: Convertible collar is one piece, measures 3" long at points and $1\frac{5}{8}$ " wide at back and is constructed of two plies of basic material and one ply of interlining. Collar lining is banana-shaped. Collar stays are of good quality vinyl that measure $2\frac{1}{2}$ " long x $\frac{3}{8}$ " wide and are attached to the bottom collar."

Sleeves: To be straight and whole. Cuffs are $2\frac{7}{8}$ " wide and fasten with two-button adjustable cuffs. There is a single stitch $\frac{1}{2}$ " from top of cuff. Sleeve opening measures $5\frac{1}{4}$ " from top of cuff. Top facing for this opening is 1 wide and bottom facing finishes about $\frac{1}{2}$ " wide.
Sleeves must be secured to the body of the shirt by a merrow stitch with a safety stitch to properly strengthen the stitch. The same stitch is used on the side closing seams.

Flex Vent: Flex Vent is made from 92% polyester/8% spandex mesh. Diamond-shaped mesh measuring $3\frac{1}{2}$ " wide x $10\frac{1}{4}$ " long is set into the sleeve and body panels at the underarm to allow body heat ventilation, increased mobility, and comfort.

Front: Front has a facing 3" wide extending from neckline to the bottom of shirt provided by a turnunder of material. Left front has a lined false top center $1\frac{1}{2}$ " wide, finished, running full length of the shirt with two rows of stitching $\frac{7}{8}$ " apart. Center front contains seven vertical buttonholes placed $\frac{3}{4}$ " from edge; first at neck, second $2\frac{1}{2}$ " down and the balance $3\frac{1}{2}$ " apart. The 3rd, 4th, 5th, and 6th buttons are sewn on the top center and are not functional.

CX360 Male Long Sleeve Shirt **Elbeco Style 3524**

Right front has a button piece, $\frac{7}{8}$ " wide, stitched the full length. The first and 6th buttons are securely attached to the button piece and correspond to the buttonholes in the center front.

Zipper: A 14" nylon zipper is sewn to the front, positioned below the second button to replace the 3rd through 6th buttons.

Dual Comm Access Openings:

Access openings measuring 1 $\frac{1}{2}$ " are set in each side seam 1" below the bottom tip of the Flex Vent. Pouch-style openings are clean-finished, neatly concealed, and reinforced for durability. Openings are used to thread communication wires under the front of the shirt to keep them out of the way.

Pockets: Two double-entry chest pockets with mitered corners finish 5 $\frac{5}{8}$ " wide x 6" long. Side entry forms a utility pocket closed with Velcro. Both pockets have 1 $\frac{1}{4}$ " box-pleats stitched from top to bottom to prevent spreading.

Flaps: Two scalloped flaps that finish 5 $\frac{3}{4}$ " long, 2 $\frac{3}{4}$ " wide at center and 2 $\frac{1}{2}$ " wide at sides are secured to front of shirt with two rows of stitching approximately $\frac{1}{4}$ " above top of pocket. Flaps are interlined and have 1 $\frac{1}{4}$ " wide pencil openings. A matching button and buttonhole are sewn on each flap.

Flap Closure: Side points of the flaps are secured to the pockets by Velcro fasteners sewn onto the flaps and pockets.

Badge Tab: Reinforced on inside of the shirt by a strip of material, 1 $\frac{1}{2}$ " wide, stitched and folded so that no raw edges show. Reinforcement strip extends from the flap setting stitch to the joining seam at the front of the yoke. There are two small horizontal buttonholes 1 $\frac{1}{4}$ " apart with the bottom hole 1 $\frac{1}{2}$ " above top of left flap.

Mic Tab: A mic tab measuring $\frac{3}{4}$ " x 2" is set 3 $\frac{1}{2}$ " below the center of the neckline.

Name Tape: An optional loose name tape measuring $\frac{7}{8}$ " wide x 8" long is set inside the right front pocket.

Buttons: All buttons, size 20 ligne, are made from high impact melamine and must match fabric.

Shoulder Straps:

Shoulder straps are pointed at the end toward the neck of the shirt. The other end is sewn in the sleeve head seam. Pointed ends are fastened with one matching button. Straps measure 2" at sleeve and taper to 1 $\frac{1}{8}$," and are set about 2" from the collar. Shoulder straps are box-stitched to shoulders with a row of cross-stitching 2" from sleeve head seam. There is a 1" concealed opening under the shoulder straps, set halfway between the neck seam and shoulder seam, to thread communication wires.

Back: Yoke, composed of an outer piece of the same material as the basic shirt and an inner

CX360 Male Long Sleeve Shirt Elbeco Style 3524

piece of poplin, is joined at the side seams with 5-thread safety stitches.

Permanent Creases:

Shirt has permanent military creases. Creases are stitched in shirt only, not through pockets and flaps. One crease in each front extends from hem to joining seam. Three vertical creases are in back; middle crease is on the center line and side creases are spaced equally from the center crease.

Creasing: Pockets and pocket flaps are die-creased to give uniform shape and size.

Interlining: Collar, cuffs, flaps, and top center are lined with non-fusible interlining for this 4-way stretch fabric.

Emblems: One Riverhead Town Police shoulder emblem shall be neatly sewn by vendor with matching thread on each left and right sleeve, $\frac{1}{2}$ " below the shoulder seam. When applicable one Sergeant chevron shall be sewn by vendor $\frac{1}{4}$ " below each Riverhead Town Police emblem. All emblems to be supplied by Police Department.

Labels: There is a heat-seal label containing brand, size, content, and country of origin in the yoke. Care label with cut number is sewn in the inside sideseam. Descriptive product hang tag is attached to front of shirt.

Pressing and Packing:

Shirts are carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are bulk-packed and shipped in strong boxes so as not to be damaged in shipment.

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	14	14$\frac{1}{2}$	15	15$\frac{1}{2}$	16	16$\frac{1}{2}$	17	17$\frac{1}{2}$	18	18$\frac{1}{2}$	19/20
Chest	39	41	43	45	47	49	51	53	55	57	63
Waist	35	37	39	41	43	45	47	50	53	55	63

**CX360 Male Long Sleeve Shirt
Elbeco Style 3524**

Back Length	32 $\frac{1}{8}$	32 $\frac{1}{4}$	32 $\frac{3}{8}$	32 $\frac{5}{8}$	32 $\frac{3}{4}$	33	33 $\frac{1}{2}$	34 $\frac{1}{2}$	34 $\frac{5}{8}$	35 $\frac{1}{2}$	36 $\frac{5}{8}$
Combination Sleeve Length:	32/33 is 33 34/35 is 35 36/37 is 37										

February 12, 2021

**Item #6: CX360 Male Short Sleeve
Shirt Elbeco Style 3544**

Style: It is the intention of this department to secure a tailored shirt equal in quality of workmanship and style to the shirt now on display as a sample. Shirt is cut on a form-fitting line, and the shape of the pockets and general style conform to this sample.

Tailoring: It is imperative that this garment is constructed according to the principles set forth in the specifications. All stitches must be of the proper tension and size to avoid puckering after the shirt has been laundered and give best durable press performance. All sewing is with Dacron core thread to match shirt fabric. Collar and cuffs are single-stitched $\frac{1}{4}$ " from edge. Pockets and flaps are single stitched on the edge.

Fabric: 100% Nanospun polyester with 16 % fiber stretch, left hand twill. Weight is 4.5 oz. per square yard. With fiber stretch, fabric maintains its stretch and recovery over time. Must be treated at the fiber level with Nano fluid repellency technology for permanent superior fluid resistance and UV 40+ protection while maintaining original fabric breathability. This fabric meets pilling test standards per ASTM 4970 of 5.0.

Color: Midnight navy

Collar: Convertible collar is one piece, measures 3" long at points and $1\frac{5}{8}$ " wide at back and is constructed of two plies of basic material and one ply of interlining. Collar lining is banana-shaped. Collar stays are of good quality vinyl that measure $2\frac{1}{2}$ " long x $\frac{3}{8}$ " wide and are attached to the bottom collar.

Sleeves: To be straight and whole, have 1" hems and finish from shoulder seams as follows:

<u>Size</u>	<u>Finished Length</u>
14 and $14\frac{1}{2}$	$9\frac{1}{2}$ "
15, $15\frac{1}{2}$, and 16	10"
$16\frac{1}{2}$ and above	$10\frac{1}{2}$ "

Sleeves must be secured to the body of the shirt by a merrow stitch with a safety stitch to properly strengthen the stitch. The same stitch is used on the side closing seams.

Flex Vent: Flex Vent is made from 92% polyester/8% spandex mesh. Diamond-shaped mesh measuring $3\frac{1}{2}$ " wide x $10\frac{1}{4}$ " long is set into the sleeve and body panels at the underarm to allow body heat ventilation, increased mobility, and comfort.

Front: Front has a facing 3" wide extending from neckline to the bottom of shirt provided by a turnunder of material. Left front has a lined false top center $1\frac{1}{2}$ " wide, finished, running full length of the shirt with two rows of stitching $\frac{7}{8}$ " apart. Center front contains seven vertical buttonholes placed $\frac{3}{4}$ " from edge; first at neck, second $2\frac{1}{2}$ " down and the balance $3\frac{1}{2}$ " apart. The 3rd, 4th, 5th, and 6th buttons are sewn on the top center and are not functional.

CX360 Male Short Sleeve Shirt **Elbeco Style 3544**

Right front has a button piece, $\frac{7}{8}$ " wide, stitched the full length. The first and 6th buttons are securely attached to the button piece and correspond to the buttonholes in the center front.

Zipper: A 14" nylon zipper is sewn to the front, positioned below the second button to replace the 3rd through 6th buttons.

Dual Comm Access Openings:

Access openings measuring 1 $\frac{1}{2}$ " are set in each side seam 1" below the bottom tip of the Flex Vent. Pouch-style openings are clean-finished, neatly concealed, and reinforced for durability. Openings are used to thread communication wires under the front of the shirt to keep them out of the way.

Pockets: Two double-entry chest pockets with mitered corners finish 5 $\frac{5}{8}$ " wide x 6" long. Side entry forms a utility pocket closed with Velcro. Both pockets have 1 $\frac{1}{4}$ " box-pleats stitched from top to bottom to prevent spreading.

Flaps: Two scalloped flaps that finish 5 $\frac{3}{4}$ " long, 2 $\frac{3}{4}$ " wide at center and 2 $\frac{1}{2}$ " wide at sides are secured to front of shirt with two rows of stitching approximately $\frac{1}{4}$ " above top of pocket. Flaps are interlined and have 1 $\frac{1}{4}$ " wide pencil openings. A matching button and buttonhole are sewn on each flap.

Flap Closure: Side points of the flaps are secured to the pockets by Velcro fasteners sewn onto the flaps and pockets.

Badge Tab: Reinforced on inside of the shirt by a strip of material, 1 $\frac{1}{2}$ " wide, stitched and folded so that no raw edges show. Reinforcement strip extends from the flap setting stitch to the joining seam at the front of the yoke. There are two small horizontal buttonholes 1 $\frac{1}{4}$ " apart with the bottom hole 1 $\frac{1}{2}$ " above top of left flap.

Mic Tab: A mic tab measuring $\frac{3}{4}$ " x 2" is set 3 $\frac{1}{2}$ " below the center of the neckline.

Name Tape: An optional loose name tape measuring $\frac{7}{8}$ " wide x 8" long is set inside the right front pocket.

Buttons: All buttons, size 20 ligne, are made from high impact melamine and must match fabric.

Shoulder Straps:

Shoulder straps are pointed at the end toward the neck of the shirt. The other end is sewn in the sleeve head seam. Pointed ends are fastened with one matching button. Straps measure 2" at sleeve and taper to 1 $\frac{1}{8}$," and are set about 2" from the collar. Shoulder straps are box-stitched to shoulders with a row of cross-stitching 2" from sleeve head seam. There is a 1" concealed opening under the shoulder straps, set halfway between the neck seam and shoulder seam, to thread communication wires.

CX360 Male Short Sleeve Shirt
Elbeco Style 3544

Back: Yoke, composed of an outer piece of the same material as the basic shirt and an inner piece of poplin, is joined at the side seams with 5-thread safety stitches.

Permanent Creases:

Shirt has permanent military creases. Creases are stitched in shirt only, not through pockets and flaps. One crease in each front extends from hem to joining seam. Three vertical creases are in back; middle crease is on the center line and side creases are spaced equally from the center crease.

Creasing: Pockets and pocket flaps are die-creased to give uniform shape and size.

Interlining: Collar, flaps, and top center are lined with non-fusible interlining for this 4-way stretch fabric.

Emblems: One Riverhead Town Police shoulder emblem shall be neatly sewn by vendor with matching thread on each left and right sleeve, $\frac{1}{2}$ " below the shoulder seam. When applicable one Sergeant chevron shall be sewn by vendor $\frac{1}{4}$ " below each Riverhead Town Police emblem. All emblems to be supplied by Police Department.

Labels: There is a heat-seal label containing brand, size, content, and country of origin in the yoke. Care label with cut number is sewn in the inside sideseam. Descriptive product hang tag is attached to front of shirt.

Pressing and Packing:

Shirts are carefully pressed by hand in first class manner and individually packed in polyethylene bags. Shirts are bulk-packed and shipped in strong boxes so as not to be damaged in shipment.

UPC Identification:

A printed UPC bar code tag must be attached to every garment to be visible in the package. The UPC bar code must identify style, color, and size information to be incorporated into an inventory management system. Appropriate support documentation must be available to assist Agency in encoding UPC information.

Code of Conduct:

All garments must be produced in acceptable non-sweatshop working conditions. Verification of acceptable working conditions are made through a completed Code of Conduct document that must be made available to the department. This document should list the location of the manufacturing companies/facilities and address child labor, wage and benefits, overtime, forced labor, freedom of association, harassment or abuse, health and safety, hours of work, non-discrimination, and no retaliation guidelines. Noncompliance of this clause is cause for rejection.

Finished Dimensions:

Size:	S	M	L	XL	2XL	3XL	4XL	5XL
Neck	14 $\frac{1}{2}$	15 $\frac{1}{2}$	16 $\frac{1}{2}$	17 $\frac{1}{2}$	18 $\frac{1}{2}$	20	22	24
Chest	41	45	49	53	57	63	71	79

CX360 Male Short Sleeve Shirt
Elbeco Style 3544

Waist	37	41	45	50	55	63	71	79
Back Length	32 $\frac{1}{4}$	32 $\frac{5}{8}$	33	34 $\frac{1}{2}$	35 $\frac{1}{2}$	36 $\frac{1}{2}$	36 $\frac{1}{2}$	36 $\frac{1}{2}$

February 12, 2021

Pricing per unit:

Item #1: CX360 Female Covert Cargo Pants Elbeco Style E3454LC \$ _____

Item #2: CX360 Male Covert Cargo Pants Elbeco Style E3444R \$ _____

Item #3: CX360 Female Long Sleeve Shirt Elbeco Style E3534LC \$ _____

Item #4: CX360 Female Short Sleeve Shirt Elbeco Style E3554LC \$ _____

Item #5: CX360 Male Long Sleeve Shirt Elbeco Style E3524 \$ _____

Item #6: CX360 Male Short Sleeve Shirt Elbeco Style E3544 \$ _____

TOTAL AMOUNT OF BID (Items 1-6): \$ _____

GENERAL MUNICIPAL LAW – SECTION 103-d

Non-Collusive Bidding Certificate

By submission of this bid, each bidder and each person signing on behalf of any bidder certifies, and in the case of a joint bid, each party thereto certifies as to its own organization, under the penalty of perjury, that to the best of his knowledge and belief:

- (A) The prices in this bid have been arrived at independently without collusion, consultation, communication or agreement, and for the purpose of restricting competition, as to any matter relating to such prices with any other bidder or with any competitor or potential competitor;
- (B) Unless otherwise required by law, the prices which have been quoted in this bid have not been knowingly disclosed by the bidder prior to the opening, directly or indirectly to any other bidder, competitor or potential competitor;
- (C) No attempt has been or will be made by the bidder to induce any other person, partnership, or corporation to submit or not to submit a bid for the purpose of restricting competition.

I hereby affirm, under the penalty of perjury, the foregoing statement is true:

Signed by: _____

Title: _____

Date: _____

Affix corporate seal if contractor is a corporation.

Sworn to before me this

_____ day of _____, 20 _____

NOTARY PUBLIC

IRAN DIVESTMENT ACT CERTIFICATION

As a result of the Iran Divestment Act of 2012 (Act), Chapter 1 of the 2012 Laws of New York, a new provision has been added to the State Finance Law (SFL), § 165-a, effective April 12, 2012. Under the Act, the Commissioner of the Office of General Services (OGS) will be developing a list (prohibited entities list) of “persons” who are engaged in “investment activities in Iran” (both are defined terms in the law). Pursuant to SFL § 165-a(3)(b), the initial list is expected to be issued no later than 120 days after the Act’s effective date, at which time it will be posted on the OGS website.

By submitting a bid in response to this solicitation or by assuming the responsibility of a Contract awarded hereunder, Bidder/Contractor (or any assignee) certifies that once the prohibited entities list is posted on the OGS website, it will not utilize on such Contract any subcontractor that is identified on the prohibited entities list.

Additionally, Bidder/Contractor is advised that once the list is posted on the OGS website, any Contractor seeking to renew or extend a Contract or assume the responsibility of a Contract awarded in response to the solicitation, must certify at the time the Contract is renewed, extended or assigned that it is not included on the prohibited entities list.

During the term of the Contract, should the TOWN OF RIVERHEAD receive information that a person is in violation of the above-referenced certification, the TOWN OF RIVERHEAD will offer the person an opportunity to respond. If the person fails to demonstrate that it has ceased its engagement in the investment which is in violation of the Act within 90 days after the determination of such violation, then the TOWN OF RIVERHEAD shall take such action as may be appropriate including, but not limited to, imposing sanctions, seeking compliance, recovering damages, or declaring the Contractor in default.

The TOWN OF RIVERHEAD reserves the right to reject any bid or request for assignment for an entity that appears on the prohibited entities list prior to the award of a contract, and to pursue a responsibility review with respect to any entity that is awarded a contract and appears on the prohibited entities list after contract award.

Signature: _____

Print Name: _____

Title: _____

Company Name: _____

Date: _____

SEXUAL HARASSMENT STATEMENT

By submission of this bid, each bidder and each person signing on behalf of any bidder certifies, and in the case of a joint bid each party thereto certifies as to its own organization, under penalty of perjury, that the bidder has and has implemented a written policy addressing sexual harassment prevention in the workplace and provides annual sexual harassment prevention training to all of its employees. Such policy shall, at a minimum, meet the requirements of §201-G of the Labor Law.

Signature: _____

Print Name: _____

Title: _____

Company Name: _____

Date: _____

Please complete and affix to your sealed bid envelope.



BIDS MUST BE DELIVERED TO THE TOWN CLERK

BIDDER: _____

ADDRESS: _____

BID NAME: POLICE UNIFORM ITEMS

BID OPENING DATE: SEPTEMBER 9, 2021

TIME: 11:00AM

BIDS MUST BE DELIVERED TO:

TOWN OF RIVERHEAD

TOWN CLERKS OFFICE

**200 HOWELL AVENUE
RIVERHEAD, NY 11901**

PRIOR TO 11AM ON SEPTEMBER 9, 2021

LATE BIDS WILL NOT BE ACCEPTED FOR ANY REASON